


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index No. V-11

History of original corner establishment:

The corner was originally established by Frank W. Campbell under Contract No. 521 dated January 8, 1885. The notes state that at the corner a 16" x 8" x 4" marked basalt stone was set 11" in the ground from which:

- A 12" fir bears N 70° W, 24 Lks (15.8 feet) marked 1/4 S BT
- A 14" fir bears S 66° E, 77 Lks (50.8 feet) marked 1/4 S BT



No record of subsequent remonumentation found in County Records .

Description of corner evidence found:

- Found a 16" x 8" x 4" basalt stone (broken in half) with "1/4" chiseled in the exposed half, from which:
- A rotted out fir stump hole bears N 68 1/2° W, 17.6 feet
- A rotted out fir stump bears S 65° E, 49.3 feet

Description of monument and accessories established to perpetuate the original location of this corner

At the corner position a 2 inch by 30 inch iron pipe, with brass cap marked as shown, was set 22 inches in the ground and surrounded with a mound of earth. Buried the marked stone beside new monument.

Set a steel fence post west of corner and attached signs 54-2 and 54-4.

Established 2 new BT's:

An 11" red fir bears N 26 1/2° W, 72.1 feet scribed 1/4 S 28 BT

An 11" red fir bears S 32° E, 28.2 feet scribed 1/4 S 33 BT

New BT's have a lower blaze scribed BT with a brass washer stamped PLS 1106 nailed flush.

Attached signs 54-3 and 54-4 and painted a 6" red band around BT's above the upper blaze.

Used steel tape and magnetic compass with 19 1/2° east declination. Measured to center of Bts.
See map of survey .


This corner set September 17, 1979

Witnesses: G. Flowers, LSIT
B. Reynolds

REGISTERED PROFESSIONAL LAND SURVEYOR

William R. Wells

OREGON JULY 22, 1977 WILLIAM R. WELLS 1106



Office of County Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 15 day of Oct 1979
Robert D. Begett by _____
(COUNTY OFFICIAL) (DEPUTY)