


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index No. Z-9

History of original corner establishment:

The corner was originally established by A. F. York under his Contract No. 309 dated November 18, 1878. The notes state that at the corner a 14" x 12" x 6" notched stone was set in a mound of stone from which:
A 31" pine bears S 50° W, 30 Lks (19.8 feet)



No record of subsequent remonumentation found in County Records .

Description of corner evidence found:

Found a 14" x 12" x 6" stone with no apparent markings, from which:
A pine stump 6 feet high with scribing visible in mostly healed blaze bears S 50° W, 19.8 feet.

Description of monument and accessories established to perpetuate the original location of this corner

At the corner position a 2 inch by 30 inch iron pipe, with brass cap marked as shown, was set 6 inches in the ground and surrounded with a mound of stones to the cap.

Set steel fence post south of corner and attached sign 54-4.

Established 4 new BT's:

An 8½" pine bears N 81° W, 34.5 feet scribed T7S R27E S 32 BT

A 10" juniper bears N 34° E, 168.0 feet scribed T7S R27E S 33 BT

A 12½" red fir bears S 6½° E, 38.1 feet scribed T8S R27E S 4 BT

An 11½" red fir bears S 45½° W, 53.0 feet scribed T8S R27E S 5BT

New BT's have a lower blaze scribed BT with a brass washer stamped PLS 1106 nailed flush.

Attached signs 54-3 and 54-4 to all BT's and painted red ring around trees above upper blaze.

Used steel tape and magnetic compass with 19½° east declination . Measured to center of Bts.

See map of survey.


This corner set September 13, 1979

Witnesses: G. Flowers, LSIT
B. Reynolds

REGISTERED PROFESSIONAL LAND SURVEYOR

William R. Wells

OREGON JULY 22, 1977 WILLIAM R. WELLS 1106



Office of County Surveyor County of Grant
State of Oregon , I hereby certify that the within Instrument was filed in this office
for record on the 15 day of Oct 1979
Robert D. Beget by _____
(COUNTY OFFICIAL) (DEPUTY)