


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Corner established in 1885 by Frank W. Campbell, under General Land Office, Contract no. 521.

Surveyor General Records states:

Set basalt stone 16x12x5 ins. for cor. to Sects. 1 & 2 marked with 1 notch on E. and 5 notches on W. and 6 notches on S. edges, from which:

- A 7" pine bears S45E, 54 lks.
- A 12" pine bears S47W, 92 lks.



No record of subsequent remonumentation was found in County Records.

Description of corner evidence found:

Found stone, call size, properly marked in mound of stone, from which:

Original BTs

- A 18" Pine, good condition, bears S37E, 34.5 ft., blaze healed.
- A 16" Pine, good condition, bears S48W, 58.2 ft., scribes visible.


Corner is on steep hillside 50 ft. North of Jones Creek.

Description of monument and accessories established to perpetuate the original location of this corner

At position of stone, I set 2 1/2"x30" iron pipe 26" in ground, raised mound of stone 8 ft. at base to top of cap.

I took no new BTs.

A North-South fence line is 35 ft. West.
 Buried stone East and along side pipe.
 Set steel fence posts 5+ ft. South and 5+ ft. East of corner.
 Used steel tape and magnetic compass with 20° E. declination.
 Measured to face of blaze on original BTs.



REGISTERED
 PROFESSIONAL
 LAND SURVEYOR

Robert D. Baggett
 OREGON
 JULY 13, 1974
 DUANE I. GRIFFITH
 644

Office of County Surveyor County of Grant
 State of Oregon, I hereby certify that the within instrument was filed in this office
 for record on the 8th day of August 1974.
Robert D. Baggett by _____
 (COUNTY OFFICIAL) (DEPUTY)

Witnessed by
Betty Rowary