


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Corner established in 1885 by Frank W. Campbell, under General Land Office, Contract no. 521.



Surveyor General Records states:

Set basalt stone 16x10x7 for cor. to Sect. 4-5, 8-9 marked with 5 notches on S. & 4 notches on E. edges, from which:

- A 12" Juniper bears N7E, 168 lks.
- A 30" Pine bears S10E, 147 lks.
- A 10" Pine bears S23W, 181 lks.
- A 12" Juniper bears N44W, 193 lks.

No record of subsequent remonumentation found in County Records.

Description of corner evidence found:

Found stone, call size, faint marks visible, in a mound of stone from which:

Original BTs.

A 14" ⁺ Juniper dead and down, badly burnt, bears N 7 E, 110.9 ft. Partial scribes visible.

A 24" Juniper, fair condition, bears N 44 W, 127.4 ft. scribes visible.

No evidence of other BTs found.

Description of monument and accessories established to perpetuate the original location of this corner


At corner position set 2½" x 30" iron post with brass cap, marked as shown, 18" in ground, raised mound of stone 7' at base to top of cap. From which, new BTs:

A 8" Juniper bears N 71 E, 195.6 ft. marked T 7 S, R 28 E, S 4 BT.

A 10" Juniper bears S 33 E, 70.7 ft. marked T 7 S, R 28 E, S 9 BT.

A 12" Pine bears S 67 W, 109.7 ft. marked T 7 S, R 28 E, S 8 BT.

Nailed brass washer to BT blazes. Buried stone south and alongside pipe. Set steel fence post 7+ ft. east of corner. Used steel tape and magnetic compass with 20° E declination. Measured to center of new BTs and face of blaze on original BTs.



**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Duane I. Griffith
OREGON
JULY 10, 1954
DUANE I. GRIFFITH
644

Office of County Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 6th day of August 1974
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)

*Witnessed by
Betty Lowrey*

E-9