


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Corner established in 1885 by Frank W. Campbell, under General Land Office, Contract no. 521.

Surveyor General Records States:

Set basalt stone 18x9x8 in. for $\frac{1}{4}$ cor. marked $\frac{1}{4}$ on N face, raised mound of stone along side.



No record of subsequent remonumentation found in County Records.

Description of corner evidence found:

Found stone, call size, firmly set in a mound of stone, marked $\frac{1}{4}$ on the North face.

Description of monument and accessories established to perpetuate the original location of this corner

In corner position, set 2 $\frac{1}{2}$ " x 30" iron pipe with brass cap marked as shown, 22" in ground, raised mound of stone 7' at base to top of cap, from which new BTs:

A 7" Juniper bears S 41 E, 86.5 ft. marked $\frac{1}{4}$ S9 BT.


A 12" Pine bears N 22 W, 59.8 ft. marked $\frac{1}{4}$ S4 T 7 S, R 28 E, BT.

Nailed brass washer in BT Blazes. Burried stone south and along side pipe. Set steel fence post 4- ft. west of corner. Used steel tape and magnetic compass with 20° E declination. Measured to center of BTs.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Handwritten signature of Duane J. Griffith

OREGON
JULY 10, 1904
DUANE J. GRIFFITH
644



Office of County Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 8th day of August
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)

Witnessed by Betty Lowary

E-11