


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Corner established in 1885 by Frank W. Campbell, under General Land Office, Contract no. 521.

Surveyor General Records states:

Set basalt stone 16x10x7 ins for cor. to Sects. 3,4,9,10 marked with 5 notches on So. & 3 notches on East edges from which:

- A 14" pine bears N40E, 47 lks.
- A 10" pine bears S71E, 231 lks.
- A 30" pine bears S69W, 79 lks.
- A 10" pine bears N63W, 75 lks.



No record of subsequent remonumentation found in County Records.

Description of corner evidence found:

Found stone, call size, properly marked, in mound of stone from which:

Original BTs.

- A 18" Pine snag bears N 40 E, 31.0 ft., scribes visible.
- A 15" Pine Stump bears S 71 E, 152.5 ft. north scribes or blaze visible.
- A 30" ⁺ Pine, dead and down, bears S 69 W, 52⁺ ft. scribes visible.
- A 15" ⁺ Pine, dead and down, badly rotted, bears N 61 W, 49.5 ft., scribes visible.


Description of monument and accessories established to perpetuate the original location of this corner

At corner position, set 2 1/2" x 30" iron pipe with brass cap, marked as shown, 25" in ground, from which:

New BTs

- A 15" Pine bears N 35 E, 130.5 ft. marked T7S R28E S3 BT
- A 14" Juniper bears S 15 E, 61.5 ft. marked T7S R28E S10 BT
- A 16" Pine bears S 42 W, 76.2 ft. marked T7S R28E S9 BT
- A 17" Pine bears N 47 W, 89.3 ft. marked T7S R28E S4 BT

Buried stone north and along side pipe. Set post 5- ft. north of corner. Used steel tape and magnetic compass with 20 E declination. Measured to center of new BTs and face of blaze on original BTs.



REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 10, 1964
DUANE I. GRIFFITH
644

Office of County Surveyor County of Grant
 State of Oregon, I hereby certify that the within instrument was filed in this office
 for record on the 8th day of August 1974.
Robert D. Baggett by _____
 (COUNTY OFFICIAL) (DEPUTY)

Witnessed by
Betty Lowary