


# CORNER RESTORATION

**CORNER:** W1/4 SEC. 12, TWP. 7 S., RANGE 30 E., W.M.

**ORIGINAL SURVEY BY:** Henry Meldrum, Deputy Surveyor

**CONTRACT NUMBER:** 380 (Joint Contract)

**CONTRACT DATE:** March 19, 1881



**ORIGINAL GLO DESCRIPTION:** Set a basalt stone 15x12x3 for 1/4 Sec cor. from which a Pine 8 in. in dia. bears S88°E, 57 lks. dist. Fir 5 in. in dia. bears S28°W, 58 lks. dist.

**EVIDENCE FOUND:** Found a basalt stone 14"x10"x3" marked 1/4. Marked stone was found lying under a down and rotting fir with two other stones. No remains of the original pine BT were found. Found a Fir stump at approximate location of the Southwest BT, but no discernable scribing was found. Area to the south has been logged multiple times.


**AT THE CORNER POINT:** I set a 1½"x30" galvanized iron pipe, with attached Grant County Surveyor brass cap, 29 inches in the ground. I buried the original marked stone inverted, South and alongside the new monument in a 3 foot mound of stone. Cap is marked as shown hereon.

**FROM WHICH I SCRIBE THE FOLLOWING NEW BEARING TREES:**

A white fir, 6" DBH, bears N.79°E., 25.54 feet, marked 1/4 S12 BT  
A ponderosa pine, 4" DBH, bears S.57°W., 19.95 feet. marked 1/4 S11 BT  
Used a total station to measure to a 50d nail driven into the side-center at the root crown of BT's and attached BT tags to BT's.

**ALSO FROM WHICH I SET THE FOLLOWING NEW REFERENCE POINTS:**

A 5/8"x30" iron pin bears N.79°40'E., 25.54 ft., with attached 1½" green plastic cap marked "GCS RP"  
A 5/8"x30" iron pin bears S.13°52'E., 17.09 ft., with attached 1½" green plastic cap marked "GCS RP"  
Used a total station to measure the reference points. Bearings are based on Geodetic North from a GPS field observation taken near the S1/4 Corner of Section 12.



**STATE PLANE COORDINATES (3601 OR N)**

Reference Datum: NAD83(2011) From OPUS solution  
Northing: 480,139.9 ft.  
Easting: 8,573,901.0 ft.  
Ellip. Ht: 4,077.5 ft.

**RESTORATION BY, STAMP AND DATE:**

Michael C. Springer, PLS, Grant County Surveyor  
Jason L. Hatfield, PLS, Deputy County Surveyor  
217 N. Canyon Blvd.  
John Day, Oregon 97845

Surveyed May 7, 2013

RECEIVED AND FILED  
GRANT COUNTY SURVEYOR

MAY 7 2013

BY: 



EXPIRES: 6/30/2014