


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

**History of original corner establishment:**

Corner was first established by William R. Gradon in 1885 under Contract No. 519, dated Octooer 2, 1884.  
 Set a basalt stone 20" X 6" X 6", 15" in the ground at Corner, with 1 notch on South and 5 notches on East edges.  
 30" Pine, N. 70° E., 106 lks., mkd. T7SR33ES29BT.  
 18" Pine, S. 10° E., 56 lks., mkd. T7SR33ES32BT.  
 30" Pine, S. 70° W., 31 lks., mkd. T7SR33ES31BT.  
 30" Pine, N. 38° W., 13 lks., mkd. T7SR33ES30BT.




**Description of corner evidence found:**

Stone 20" X 6" X 6", with 5 notches and 1 notch, out of ground and on side.  
 32" D.B.H. (30") Ponderosa Pine, N. 72½° E. 70.8', (N. 70° E., 106 lks.) with scribes 33ES29 visible on an open face.  
 S.E. B.T. position falls in road. Gone.  
 34" D.B.H. (30") Ponderosa Pine, S. 70° W., 31 lks., with scribes R33S31 visible on an open face.  
 34" D.B.H. (30") Ponderosa Pine, N. 38° W., 13 lks., with scribes 33S3 visible on an open face.

**Description of monument and accessories | established to perpetuate the original location of this corner:**

Set a 2½" diam. alum. cap in a 2½" X 30" alum. pipe at intersection of bearings & distances from N.W. & S.W. B.T's.. N.E. B.T. does not fit. N.W. & N.E. B.T. faces do not face Corner.. Measured from chaining notches.  
 Cap mkd. per sketch. Set steel posts 3'± E. & W. with mon. and attn. signs attached.  
 12" D.B.H. Ponderosa Pine, S. 27° E., 86.1', scribed T7SR33ES32BT.  
 Cornerstone buried alongside Monument.  
 Declination; 18° 45' East..

T7S R33E  
 S30 | S29  
 S31 | S32  
 RPLS 1910  
 1985



*Clayton J. Martin*



C.J. MARTIN SURVEYING  
 2751 JUNIPER ST.  
 SWEET HOME, OR 97386

Office of Surveyor County of Grant  
 State of Oregon, I hereby certify that the within instrument was filed in this office  
 for record on the 13 day of Aug, 1985  
Robert D. Bayett by \_\_\_\_\_  
 (COUNTY OFFICIAL) (DEPUTY)