

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:


The corner was originally established by Eugene McGornack under Contract No. 398 dated July 2, 1882.

The original notes state that at the corner:

A 20 in. by 12 in. by 12 in. marked Sand stone, set 15 in. in the ground for the corner, from which:

A 8 in. dia. Pine bears N20°E - 18 lks (11.9 ft.) marked: T7S R35½E S21 BT

A 10 in. dia. Spruce bears S50°E - 12 lks (7.9 ft.) marked: T7S R35½E



See attached sheet for history of 1974 BLM remonumentation.

Description of corner evidence found:

A 3¼ in. dia. brass cap on an iron pipe, in small mound of stone, marked as per diagram, set by BLM - 1974, from which:

A 9½ in. dia. Lodgepole Pine snag bears N20°E - 18 lks (11.9 ft.) with visible scribing

A 10½ in. W. Fir snag bears S50°E - 12 lks (7.9 ft.) with visible scribing.

A 8½ in. down L.P. Pine bears S86½°W - 4.5 ft. with visible scribing.

A 10 in. W. Fir bears N48°E - 59½ lks (39.3 ft.) with visible scribing.

Description of monument and accessories established to perpetuate the original location of this corner:

Set: A 7 in. W. Fir bears S75°E - 28.2 ft., scribed: T7S R35½E S28 BT.

Each new bearing tree has a brass washer stamped PLS 1106 nailed to the face of the blaze, and has 54-3 and 54-4 signs attached. Painted face of blaze and a 6 in. band around each bearing tree red.

Set a steel fence post, with 54-4 sign attached, North of the monument.

Used a steel tape and a magnetic staff compass, with 20° East declination. Measured to the center of the bearing trees.

This corner was maintained on September 15, 1983.

Witnessed by: Robert D. English
Aaron C. Hoeft

REGISTERED
PROFESSIONAL
LAND SURVEYOR

William R. Wells

OREGON
JULY 22, 1977
WILLIAM R. WELLS
1106

Office of..... County Surveyor..... County of..... Grant.....
State of..... Oregon....., I hereby certify that the within instrument was filed in this office
for record on the 15 day of Oct, 1984
Robert D. English by
(COUNTY OFFICIAL) (DEPUTY)