

-History of 1974 BLM Remonumentation-

The cor. of secs. 21 and 28 only, on the W. bdy. of the Tp., monumented with the original sandstone, 20 x 12 x 12 ins., firmly set 3 ins. in the ground, mkd. with 4 grooves on N. face and 2 grooves on S. face, from which the original bearing trees:

A lodgepole pine, 11 ins. diam., bears N. 20° E., 18 lks. dist., with scribe marks T7S R35½E S21 BT visible on partially healed double blaze. (Record, 62 lks.)

An Engelmann spruce, 12 ins. diam., bears S. 30° E., 12 lks. dist., with scribe marks 7S R35½E S28 BT visible on partially healed double blaze.

and a tree of which I have no record

A lodgepole pine, 9 ins. diam., bears S. 81° W., 7 lks. dist., with scribe marks T7S R35E S25 BT visible on open double blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 7 S		T 7 S
R 35 E		S 21
		S 28
S 25		R 35½ E
		1974

from which a new bearing tree

A subalpine fir, 11 ins. diam., bears N. 48° E., 59½ lks. dist., mkd. T7S R35½E S21 BT.

Bury the corner stone alongside iron post.