

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


History of original corner establishment:

Corner was established by Eugene P. McCornack, U.S. Deputy Surveyor, during the original survey dated July, 1882.

Set Basalt stone 12x8x6 ins. 8 ins. in the ground for Cor. to Secs. 19, 30, 24 & 25 marked with 4 notches on the N and 2 notches on S edges from which

- A Pine 12ins. diam. bears N70°W, 20 lks.(13.2') dist. marked T7SR35¹/₂E S24 BT
- A Pine 12ins. diam. bears N35°E, 16 lks.(10.6') dist. marked T7SR36E S19 BT
- A Pine 8ins. diam. bears S40°E, 20 lks.(13.2') dist. marked T7SR36E S30 BT
- A Pine 12ins. diam. bears S65°W, 24 lks.(15.8') dist. marked T7SR35¹/₂E S25 BT

DIAGRAM



1985
RLS 699

Description of corner evidence found:

12x8x6 stone set firmly in the ground. Could not find any clear chisel marks on the stone.

- 12" Lodgepole pine (Dead)(Scribing Visible)(1882 BT) bears N72° 15'W, 13.3 feet.
- The 12" Pine, 8" Pine, and 12" Pine (1882 BTs) were not found.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 3/4" aluminum cap, marked as shown in the diagram, 26" in the ground, replacing the rock which is turned upside down and buried on the north side of the monument. Built a mound of earth & rock to be 36" in diameter by 4" high around the monument, from which new BTs are:

- 9" Lodgepole pine bears S15°W, 15.8 feet scribed T7SR35¹/₂E S25 BT
- 11" Englemann spruce bears N51° 30'W, 33.7 feet scribed T7SR35¹/₂E S24 BT
- 7" Lodgepole pine bears N16° 45'E, 5.2 feet scribed T7SR36E S19 BT
- 6" Lodgepole pine bears S3° 45'E, 16.6 feet scribed T7SR36E S30 BT

Sawed off the dead BT about 6" above the ground. Attached BT and Attention signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being a solar observation, to the scribed blazes which were painted red. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set a steel fence post 5 feet N of the corner with an Attention sign attached. This corner is not on a property line.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on July 18, 1985, I monumented the corner as herein described.

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 16 DAY OF OCT, 1985

Robert D. Bayliff
Co. Sur.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Leland L. Myers

OREGON
JULY 9, 1965
LELAND LEE MYERS
699

See MAP OF SURVEY NO. 892