CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1884 by William Barr, Under General Land Office Contract No. 492. Surveyor Generals Notes state:
Set basalt stone 12x10x6" 8" in the ground for ¼ section corner marked ¼ on W face, From which:
A Pine 8" dia. bears N75°E, 5 lks dist. marked ¼ S BT.
A " 6" " " S10°W, 16 " " " " " "

DIAGRAM

T7S R35½E
¼
S33 ! S34
1983
PLS848

Description of corner evidence found:

Found a 11"x10"x5" stone with ¼ chiseled on face, lying loose.
Found dead Lodge-pole Pine 8" dia. standing with scribing reads ¼ S BT.
Established ¼ corner position at record S75°W, 3.3 ft. from that tree
(2 ft. South of loose stone)

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30"x2½" aluminum pipe with a 2½" aluminum cap stamped as shown in diagram.
Set 26": in the ground and set original stone North alongside pipe.
From which:
A Lodge-pole Pine 7" dia. bears N38°E, 46.3 ft. scribed ¼ S34 BT.
A Tamarack 18" " " S55°W, 38.3 ft. " " S33 "
Set steel posts with warning and boundry signs North 4 ft. and South 4 ft.
Nailed brass washers stamped PLS848, bearing tree and warning signs to each tree.
Painted 6" red band around each tree.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Corner monumented 8-29-83

Witnessed by Dan Martin

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 22 day of Nov, 19 83
Robert D Baggett by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

GPO—798-276

X-13