


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

**History of original corner establishment:**

Corner not previously established.



**Description of corner evidence found:**

N/A

**Description of monument and accessories I established to perpetuate the original location of this corner:**

Set a 30"x2½" aluminum pipe with a 2½" aluminum cap stamped as shown in diagram.  
 Set 14" in the ground and raised a mound of stone around pipe.  
 From which:  
 A Lodge-pole Pine 14" dia. bears S83°W, 69.4 ft. scribed C-E 1/16 S34 BT.  
 A " " " 5" dia. bears S75½°E, 17.7 ft. scribed 1/16 BT.  
 C-E S34 omitted on small tree.  
 Set steel posts with warning and boundry signs South and West 5 ft.  
 Nailed brass washers stamped PLS848, bearing tree and warning signs to each tree.  
 Painted 6" red band around each tree.

Corner monumented 8-30-83

Witnessed by Dan Martin

REGISTERED  
 PROFESSIONAL  
 LAND SURVEYOR

OREGON  
 JULY 12, 1968  
 DOUGLAS M. FERGUSON  
 848

Office of Sumner County of Grant  
 State of Oregon, I hereby certify that the within instrument was filed in this office  
 for record on the 22 day of Nov, 1983  
Robert D. Baggett by \_\_\_\_\_  
 (COUNTY OFFICIAL) (DEPUTY)