

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1884 by William Barr, Under General Land Office Contract No. 492. Surveyor Generals Notes State: Set granite stone 14"x10"x6", 10" in ground for 1/4 sec. corner, marked 1/4 on W face.

From Which:

A Pine 12" dia. bears N65°W, 33 lks dist. marked 1/4 S BT.
A Pine 12" dia. bears N20°E, 10 lks dist. marked 1/4 S BT.

DIAGRAM

T7S R35 1/2 E
170
1/4
S34 | S35
1983
PLS848

Description of corner evidence found:

No trace of original stone found, area shows a lot of activity in the past, an old garbage trench is situated just SW from corner. No evidence of the original trees found, they were probably mature when scribed and being Lodge-pole have died & decayed away the original notes call for Onion Creek 5.75 ch. South & the North Fork of the John Day River 7.70 ch. North, since at the position on line between the NE&SE corner of sec. 35 Onion Creek & the river are as nearly as can be determined 13.45 ch. between them, therefor the N-S position of the corner is determined by those topography calls. E-W position is on line between the said NE&SE corners of sec. 35.

Description of monument and accessories established to perpetuate the original location of this corner:


Set a 30"x2 1/2" aluminum pipe with a 2 1/2" aluminum cap stamped as shown in diagram. Set 28" in the ground.

From which:

A Lodge-pole Pine 7" dia. bears N33°E, 29.1 ft. scribed 1/4 S35 BT.
A " " " 10" " " N77°W, 21.5 ft. " " S34 "


Set steel post with warning sign 2.5 ft. North.

Nailed brass washers stamped PLS848, bearing tree and warning signs to each tree. Painted 6" red band around each tree.



Corner monumented 8-29-83

Witnessed by Dan Martin



Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 22 day of Nov, 1983
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)