

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established by Herman D. Gradon, under contract No. 499 dated March, 1884.

The original notes state that at the corner:


A 4 in. square by 4 ft. marked post, set 24 in. in the ground for the corner, from which:

A 16 in. dia. Pine bears N30°E - 37 lks (24.4 ft.), marked: T7S R35E S12 BT

A 8 in. dia. Pine bears S88°E - 20 lks (13.2 ft.), marked: T7S R35E S13 BT

A 8 in. dia. Pine bears S44°W - 11 lks (7.3 ft.) marked: T7S R35E S14 BT

A 10 in. dia. Pine bears N30°W - 19 lks (12.5 ft.) marked: T7S R35E S11 BT



No record of subsequent remonumentation was found in County records.

Description of corner evidence found:

A 14 in. dia. Pine snag bears S88°E - 20 lks (13.2 ft.) with partially open blaze.

A 10½ in. dia. Pine snag bears N30°W - 19 lks (12.5 ft.) with open blaze and visible scribing.

Reset corner by distance-distance intersection from the two found bearing trees.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set: A 2½ in. by 30 in. aluminum pipe, with a 2½ in. aluminum cap, 26 in. in the ground with a mound of stone to the cap, from which:

A 12 in. dia. Lodgepole Pine bears N55°E - 124.6 ft., scribed: T7S R35E S12 BT

A 16 in. dia. Lodgepole Pine bears N80½°W - 83.7 ft., scribed: T7S R35E S11 BT

A reference monument bears S46°W - 12.00 ft., marked: S14 ↗ 12.00 ft. 1106

A reference monument bears S17½°E - 12.00 ft., marked: S13 ↖ 12.00 ft. 1106

Note: A reference monument is a 1½ in. aluminum cap on a 5/8 in. by 30 in. iron pin.

Set steel fence posts (guard posts) with 54-4 signs attached near reference monuments. Each new bearing tree has a brass washer stamped PLS 1106 nailed to the face of the blaze, and has 54-3 and 54-4 signs attached. Painted the face of the blaze and a 6 in. band around each bearing tree red.

Set a steel fence post, with 54-4 sign attached, North of the monument. Used a steel tape and a magnetic staff compass, with 20° East declination. Measured to the center of the bearing trees.


This corner was monumented on September 13, 1983.

Witnessed by: Robert D. English
Aaron C. Hoefl

REGISTERED
PROFESSIONAL
LAND SURVEYOR

William R. Wells
OREGON
JULY 22, 1977
WILLIAM R. WELLS
1106

Cap marked:



Office of County Surveyor..... County of..... Grant
State of... Oregon....., I hereby certify that the within instrument was filed in this office for record on the 15 day of Oct, 1983
Robert D. English by
(COUNTY OFFICIAL) (DEPUTY)