

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established by Herman D. Gradon, under contract No. 499 dated March, 1884.

The original notes state that at the corner:

A 18 in. by 18 in. by 14 in. marked Basalt stone set 12 in. in the ground for the corner, from which:

A 24 in. dia. Fir bears N70°E - 63 lks (41.6 ft.)

marked: T7S R35E S14 BT

A 10 in. dia. Fir bears S58°E - 72 lks (47.5 ft.)

marked: T7S R35E S23 BT

A 6 in. dia. Pine bears S35°W - 134 lks (88.4 ft.)

marked: T7S R35E S22 BT

No trees available in Northwest quadrant.


No record of subsequent remonumentation found in County records.

Description of corner evidence found:

A 32 in. dia. Fir bears N73°E - 63 lks (41.6 ft.) with healed blaze.

A 20 in. dia. Fir bears S58°E - 72 lks (47.5 ft.) with healed blaze.

Corner was re-established by distance-distance intersect from the found bearing trees.



Description of monument and accessories I established to perpetuate the original location of this corner:

Set: A 2½ in. by 30 in. aluminum pipe, with a 2½ in. aluminum cap, 20 in. in the ground with a mound of stone to the cap, from which:

A 12 in. dia. Fir bears S12°E - 28.0 ft., scribed: T7S R35E S23 BT

A 7½ in. dia. Fir bears S12°W - 35.4 ft., scribed: T7S R35E S22 BT

A reference monument bears N45°W - 12.00 ft., marked: S15 12.00 ft. PLS 1106

Each new bearing tree has a brass washer stamped PLS 1106 nailed to the face of the blaze, and has 54-3 and 54-4 signs attached. Painted face of blaze and a 6 in. band around each bearing tree red.

Reference monument is a 5/8 in. iron pin with 1½ in. aluminum cap. Set steel fence post next to monument with sign 54-4 attached.

Set a steel fence post, with 54-4 sign attached, North of monument.

Used a steel tape and a magnetic staff compass, with 20° East declination. Measured to the center of the bearing trees.

This corner was monumented on September 7, 1983.


Cap marked:

Witnessed by: Robert D. English
Aaron C. Hoelt

REGISTERED
PROFESSIONAL
LAND SURVEYOR

William R. Wells

OREGON
JULY 22, 1977
WILLIAM R. WELLS
1106



Office of.....County Surveyor..... County of.....Grant.....

State of.....Oregon....., I hereby certify that the within instrument was filed in this office

for record on the 15 day of Oct, 1983

Robert D. English by

(COUNTY OFFICIAL)

(DEPUTY)