

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Amended Monument

History of original corner establishment:


Corner established by Herman D. Gradon, under contract No. 499 dated March, 1884.

The original notes state that at the corner:

A 4 in. square by 4 ft. marked post, set 24 in. in the ground for the corner, from which:

A 6 in. dia. Pine bears S65°W - 58 lks (38.3 ft.) marked: T7S R35E S24 BT

A 8 in. dia. Pine bears N28°W - 8 lks (5.3 ft.) marked: T7S R35E S13 BT



For history of 1974 BLM remonumentation, see attached sheet.

Description of corner evidence found:

A 3 $\frac{1}{4}$ in. brass cap on an iron pipe, in a mound of stone, set by BLM in 1974, marked as per diagram, from which:

A 5 in. dia. downed l.p. pine bears S41°W - 63 lks (41.6 ft.), with visible scribing.

A 8 in. dia. downed l.p. pine bears N60°W - 50 lks (33.0 ft.), with visible scribing.

A 12 in. dia. down l.p. pine bears S65°W-58lks (38.3 ft.), with visible scribing.

Description of monument and accessories I established to perpetuate the original location of this corner:

A 6 in. dia. Lodgepole Pine bears S45°W - 26.4 ft., scribed: T7S R35E S24 BT
A reference monument bears N32°W - 15.00 ft., marked: S13 15.00 ft. 1106

Set a steel fence post (guard post), with a 54-4 sign attached, near reference monument.

Note: A reference monument is a 1 $\frac{1}{2}$ in. aluminum cap on a 5/8 in. iron pin.

Each bearing tree has a brass washer stamped PLS 1106 nailed to the face of the blaze, and has 54-3 and 54-4 signs attached. Painted the face of the blaze and a 6 in. band around each bearing tree red.

Set steel fence post West of the monument with 54-2 and 54-4 signs attached,

Used a steel tape and a magnetic staff compass, with 20° East declination. Measured to the center of the bearing trees.

This corner was maintained on September 15, 1983.

Witnessed by: Robert D. English
Aaron C. Hoelt

REGISTERED PROFESSIONAL LAND SURVEYOR

William R. Wells

OREGON JULY 22, 1977 WILLIAM R. WELLS 1106

"AM" for Amended Monument was stamped on the BLM cap as shown on the diagram.

Office of... County Surveyor..... County of... Grant
State of... Oregon....., I hereby certify that the within instrument was filed in this office
for record on the... 15... day of... Sept... 1984
..... by

(COUNTY OFFICIAL)

(DEPUTY)