


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

O-24

History of original corner establishment:

1983, William R. Wells, PLS 1106, in Grant County Survey No. 836, established this corner when he subdivided the section. Wells set a 2 1/2" by 30" aluminum pipe, with a 2 1/2" aluminum cap, 22" in the ground, from which:
Reference monument, 1 1/2" aluminum cap on 5/8" rebar, bears N. 42 1/2° W., 12.00 feet.
Reference monument, 1 1/2" aluminum cap on 5/8" rebar, bears N. 42° E., 12.00 feet.



Description of corner evidence found:

Found a 2 1/2" aluminum pipe, with 2 1/2" aluminum cap, projecting 4" out of the ground, from which:
5/8" rebar, projecting 4" out of the ground, bears N. 42 1/2° W., 12.00 feet (1 1/2" aluminum cap is missing).
5/8" rebar, with 1 1/2" aluminum cap, projecting 2" out of the ground, bears N. 42° E., 12.00 feet, marked "S24 12.00 FT 1106" with arrow pointing toward corner.

Description of monument and accessories I established to perpetuate the original location of this corner:

Magnetic Declination: 20° East

Worked performed by: David A. Schlaich (RLS 2308)
Date: October, 1993

REGISTERED
PROFESSIONAL
LAND SURVEYOR

David A. Schlaich

OREGON
JULY 16, 1987
DAVID A. SCHLAICH
2308

Expires 12/31/94

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 2 day of Feb, 1994
Robert D. Bagen by _____
(COUNTY OFFICIAL) (DEPUTY)