

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established by Herman D. Gradon, under contract No. 499 dated March, 1884.

The original notes state that at the corner:

A 4 in. square X 4 ft. marked post set 24 in. in the ground for the corner, from which:

A 6 in. dia. Pine bears N58°E - 16 lks (10.6 ft.) marked: T7S R35E S24 BT

A 7 in. dia. Pine bears S59°E - 29 lks (19.1 ft.) marked: T7S R35E S25 BT


A 12 in. dia. Pine bears S35°W - 55 lks (36.3 ft.) marked: T7S R35E S26 BT

A 8 in. dia. Pine bears N50°W - 46 lks (30.4 ft.) marked: T7S R35E S23 BT

No record of subsequent remonumentation was found in County records.

Description of corner evidence found:

None



Re-established corner by survey using the double proportion method between four found corners, the SW corner section 23, SE corner section 24, NW corner section 24, and West 1/4 corner section 25.

Spent 14 manhours (5 hours PLS time) searching a 300 ft. radius around this corner. Corner falls in an area that has been heavily cut for firewood. Record topo calls to our corner position match record topo calls to Trout Creek to the North and East within about 20 feet.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set: A 2½ in. X 30 in. aluminum pipe, with a 2½ in. aluminum cap, 24 in. in the ground with a mound of stone to the cap, from which:


- A 9 in. dia. L.P. Pine bears N68°E - 99.2 ft. scribed: T7S R35E S24 BT
- A 8½ in. dia. L.P. Pine bears S58½°E - 138.7 ft. scribed: T7S R35E S25 BT
- A 9½ in. dia. L.P. Pine bears S43½°W - 88.6 ft. scribed: T7S R35E S26 BT
- A 17 in. dia. Spruce bears N75°W - 36.2 ft. scribed: T7S R35E S23 BT

Each new bearing tree has a brass washer stamped PLS 1106 nailed to the face of the blaze. Attached signs 54-3 and 54-4 and painted the face of the blaze and a 6 in. red band around each bearing tree.

Set a steel fence post with 54-4 sign attached, North of the monument.

Used a steel tape and a magnetic staff compass, with 20° East declination. Measured to the center of the bearing trees.

Cap marked:



This corner was monumented on September 6, 1983.

Witnessed by: Robert D. English
Aaron C. Hoeft

REGISTERED
PROFESSIONAL
LAND SURVEYOR

William R. Wells

OREGON
JULY 22, 1977
WILLIAM R. WELLS
1106

Office of.....County...Surveyor..... County of.....Grant
State of.....Oregon....., I hereby certify that the within instrument was filed in this office
for record on the...15...day of...Sept...1983
Robert D. English by
(COUNTY OFFICIAL) (DEPUTY)