

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


T-5

History of original corner establishment: Corner established by Herman D. Gradon on September 12, 1884, under Contract No. 499:

Set a post 3 inches square, 3 feet long marked for the corner, from which:

A pine, 10 inches in diameter, bears S65°E, 12 links (7.92 feet) scribed "¼ S BT"

A tamarack, 6 inches in diameter, bears N67°W, 14 links (9.24 feet) scribed "¼ S BT"



Description of corner evidence found: Original 10 inch pine is now a 14" lodgepole pine with scribes "¼ S BT" visible on a partly healed blaze, bears S61°30'E, 9.24 feet. Original 6" tamarack is now down and decayed. Scribes "¼ S BT" are visible on the partly healed blaze. The stump hole at the original position of this tree bears N71°W, 7.92 feet.

Description of monument and accessories I established to perpetuate the

original location of this corner: By reference to the original bearing trees, I set a 2½" x 30" brass capped iron pipe 27" into the ground. The brass cap is marked:

From which:

A 12 inch western larch bears S53°W, 9.9 feet scribed "¼ S30 BT" on a single blaze. I nailed a 3/4" brass washer, marked "PLS 1636" flush on the lower portion of the blaze.

T7S R35E
¼
S30 | S29
PLS 1636
1984

Both standing bearing trees have a 54-3, bearing tree, and a 54-4, attention sign attached.

I hereby certify the above corner point was perpetuated as hereon described on August 28, 1984.

Witnesses: Susan E. Newstetter
Cathy M. McGuire. De: 18°E

REGISTERED PROFESSIONAL LAND SURVEYOR
Dennis L. Gaylord
OREGON
JULY 14, 1978
DENNIS L. GAYLORD
1636

Office of..... County Surveyor..... County of..... Grant
Oregon
State of....., I hereby certify that the within instrument was filed in this office
for record on the 24 day of Sept, 1984
Robert D. Grant by
(COUNTY OFFICIAL) (DEPUTY)