CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Refer to: Plat of Wilson 1985 Cadastral Survey
Section 29, T.7S., R.27E., W.M.

History of original corner establishment:

No record of previous monumentation.

DIAGRAM

T7S R27E
S29
C-S-SW-NE
1/256

Description of corner evidence found:

None.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the corner point I set a 2½"X 30" alum. pipe with a 3" alum. cap containing a magnet and marked:

S29
C-S-SW-NE
1/256
PLS 1832
1986

I built a stone mound around the monument.

From the corner:
A Ponderosa Pine, 7" dia., N84½°E, 27.0 ft.
marked: C S SW NE 1/256 S29 BT
A Ponderosa Pine, 8" dia., N21½°E, 24.2 ft.
marked: X at breast height and BT at base.
A Ponderosa Pine, 12" dia., N53°E, 33.3 ft.
marked: C S SW NE 1/256 S29 BT
A Ponderosa Pine, 12" dia., N8°W, 27.3 ft.
marked: C S SW NE 1/256 S29 BT

BTs have blaze and a 6" stripe painted red, a BT tag, a "Land Survey Monument" sign and an alum. "PLS 1832" washer nailed to the bottom of the blaze. There is a 6' steel fence post with a "Land Survey Monument" sign within 5' of the corner.

Measured to center of BTs using steel tape and staff compass. Magnetic declination set at 18°E.

April 13, 1986 / July 1, 1986 add BTs.

REGISTERED PROFESSIONAL LAND SURVEYOR
Fayette S. Munro
OREGON
JULY 13, 1979
FAYETTE S. MUNRO
1832

Office of Lamoyer County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 25 day of July, 19 86
Doreen D. Slagle by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

GPO—798-276

S¾-7½