CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index No. V-13

DIAGRAM

T7S	R27E
S28	S27
S33	S34

W.M.

History of original corner establishment:

The corner was originally established by Frank W. Campbell under Contract No. 521 dated January 8, 1881. The notes state that at the corner a 16" x 8" x 7" notched basalt stone was set 11" in the ground from which:
A 36" pine bears N 20° E, 106 Lks (67.0 feet) marked T7S R27E S 27 BT
A 24" pine bears S 73° E, 31 Lks (20.5 feet) marked T7S R27 E S 34 BT
A 12" pine bears S 3° W, 14 Lks (9.2 feet) marked T7S R27E S 33 BT
A 24" pine bears N 65° W, 92 Lks (60.7 feet) marked T7S R27E S 28 BT

No record of subsequent remonumentation found in County Records .

Description of corner evidence found:

Found no evidence of original stone. A recent stone mound bears S 70° E, 3 feet from our monument which was set from original bearing trees.
Found the following original bearings trees:
A down and rotten pine bears N 20° E, 70.0 feet to stumphole, scribing burned off.
A down and rotten pine bears S 73° E, 20.5 feet to stumphole, scribed T7S R27E S 34 BT.
A down and rotten pine bears S 8° W, 6 feet + scribed T7S R27E S 33 BT (no trace of stumphole).
A down and rotten pine bears N 68° W, 60.7 feet to stumphole scribed T7S R27E S 28.

Description of monument and accessories I established to perpetuate the original location of this corner

At the corner position a 2 inch by 30 inch iron pipe, with brass cap marked as shown, was set 18 inches in the ground and surrounded with a mound of stones to the cap.
Set steel fence post south and west of corner and attached signs 54-2 and 54-4 to one post and sign 54-2 to the other post.
Established 4 new BT's:
An 8" red fir bears N 45° E, 10.3 feet scribed T7S R27E S 27 BT (tree also has a line blaze chest high)
A 9" red fir bears S 28½° E, 25.9 feet scribed T7S R27E S 34 BT
A 9½" red fir bears S 82½° W, 39.1 feet scribed T7S R27E S 33 BT (tree has healed line blaze on south side)
A 9½" red fir bears N 57½° W, 29.1 feet scribed T7S R27E S 28 BT
New BT's have a lower blaze scribed BT with a brass washer stamped PLS 1106 nailed flush.
Attached signs 54-3 and 54-4 to all BT's and painted red ring around trees above upper blaze.
Used steel tape and magnetic compass with 19½° east declination. Measured to center of Bts.
See map of survey.

This corner set September 18, 1979

Witnesses: G. Flowers, LSIT
B. Reynolds

REGISTERED
PROFESSIONAL
LAND SURVEYOR

William R. Wells

OREGON
JULY 22, 1977
WILLIAM R. WELLS
1106

T7S R27E
S28 | S27
S33 | S34
1979
PLS 1106

Office of County Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 15 day of Oct 1979.
Colleen D Sagers (COUNTY OFFICIAL) by (DEPUTY)

Form R6-7100-57 (9/71)

GPO 796-333

V-13