CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

DIAGRAM

T6S R33E

S	32

Corner originally established by Frank W. Campbell under GLO contract number 468, dated April 12, 1883. Surveyor General record states:

Set a granite stone 16x10x4 ins 11 ins in the ground for ¼ sec cor marked ¼ on N face from which:
A pine 40 in diam bears N68°W 41 lks dist marked ⅛S BT
A pine 36 in diam bears S36°E 91 lks dist marked ⅛S BT
Corner remonumented in 1977 by Craig L. Wanless, BLM Group no. 350. His notes state; The ¼ cor of secs 5 and 32, on the S boundary of the Tp monumented with the original unmarked granite stone, 16x10x4 ins firmly set 4 ins in the ground in a collar of stones, from which the remains of the original bearing trees; A sawed pine stump, 41 ins diam, bears N68°W 41 lks dist with scribes visible. A pine snag 38 ins diam bears S36°E 91 lks dist with scribes visible. At the corner point set an iron post in a mound of stone 2 ft base to top with brass cap marked; (markings shown below) from which new bearing trees: A pine 10 ins diam bears N14°W 32 lks dist marked ¼ S32 BT.
A pine 10 ins diam bears S27°W 47 lks dist marked ¼ S5 BT.
Deposit corner stone alongside iron post.
No record of subsequent monumentation found in Umatilla County survey records.

Description of corner evidence found:

Found a standard BLM brass cap marked as shown, in a mound of stone.

Original BTs:
Found an 34 inch diameter pine snag S36°E, 91 lks dist, dead and standing with blaze evident.
Found a 39 inch diameter Pine stump N68°W, 41 lks dist, rotting with scribes visible.

BLM BTs:
Found a 12 inch diameter Douglas Fir S27°E, 47 lks dist, sick and dying with blaze evident.
Found a 14 inch diameter Douglas Fir N14°W, 32 lks dist, sick and dying with blaze evident.



NOTE:
BLM record states taking pine bearing trees.

Description of monument and accessories I established to perpetuate the original location of this corner: From the existing found BLM brass cap monument:

New BTs:

A 10 inch diameter Ponderosa Pine bears N17°E, 43.68 feet marked ¼ S32 BT
A 10 inch diameter Ponderosa Pine bears S18°E, 70.84 feet marked ¼ S5 BT

Painted a 6 inch red band around all BTs and attached 54-3 and 54-9 signs.

Set a steel fencepost approximately 5 feet East with 54-2 and 54-9 signs attached.

I hereby certify that the above corner point was perpetuated as hereon described on July 21, 1987.

Witness: Rick Robinson

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 10, 1964
DUANE I. GRIFFITH
644

I used a steel tape and magnetic compass in the establishment of new accessories. I used 17° East magnetic declination and the distances are to a 50d spike driven in the right side of the root crown. I attaached a brass washer marked OPLS 644 to the BT blaze.

Office of Surveyor *County of* Grant
State of Oregon, *I hereby certify that the within instrument was filed in this office for record on the* 26 *day of* Aug, *19* 87
Robert D Baggett *by* .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆GPO—798-276

1-7

Z-7

A-7