CERTIFIED RECORD OF LAND CORNER MONUMENTATION

B - 1

History of original corner establishment:

In 1978, David H. Krumbein, PLS 933, set a 2 1/2" iron pipe with a brass cap marked as shown in the diagram, from which: A 16" Pine bears N37°W, 11.25 feet.
A 14" Pine bears S86°E, 31.7 feet.
On August 12, 1989, Fayette S. Munro, PLS 1832, found the corner as described above, except the 14" Pine which bears S86°E is dead. Munro scribed the follwing new bearing tree:
A 17" Ponderosa Pine bears S18°15'E, 52.0 feet.

DIAGRAM

T7S
N 1/16
S1 S6
R32E R33E
1978
PLS 933

Description of corner evidence found:

A 2 1/2" iron pipe with a 2 1/2" brass cap attached which is marked as shown in the diagram above. The cap is protruding 8" and the pipe is surrounded by a mound of stones, from which:
A 17" Ponderosa Pine with charred scribes visible is sickley. Bears N38°W, 11.3 feet.
A down and burnt Ponderosa Pine with no marks remaining, stump hole bears S86°E, 31.7 feet.
A 17" Ponderosa Pine with charred scribes visible on a single blaze bears S19°15'E, 52.0 feet.

Description of monument and accessories I established to perpetuate the original location of this corner:

I scribe the following new bearing tree:
A 18" Ponderosa Pine scribed "N 1/16 S1 BT" on double blazes bears S77°45W, 44.2 feet. This tree has a 3/4" brass washer, marked "PLS 1636", nailed flush to the lower blaze, a 54-3, "Bearing Tree", sign nailed above the blazes and a 54-9, "Land Survey Monument", sign nailed to the back.

I hereby certify the above corner point was perpetuated as hereon described on March 11, 1997. Magnetic declination: 20°E.

REGISTERED PROFESSIONAL LAND SURVEYOR
OREGON
JULY 15, 1978
DENNIS L. GAYLORD
1636

Dennis L. Gaylord
Renews 6/30/97

Office of [redacted] *County of* [redacted]
State of [redacted], *I hereby certify that the within instrument was filed in this office for record on the* 7th *day of* April, 19 97
Robert D. Rogers *by* .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

GPO—791-311