CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Unsurveyed- Subdivided Section

DIAGRAM
T 7S R 33E
C $\frac{1}{4}$

No record of subsequent remonumentation found in County Records.

Description of corner evicence found:

NONE.

Description of monument and accessories I established to perpetuate the original location of this corner

Set 2½" x 30" iron pipe 26" in ground with brass cap marked as shown from which I scribed bearing trees.

A pine 11in. diam. brs. N 29°51' E 49.25ft. marked C $\frac{1}{4}$ S6 BT
A pine 12in. diam. brs. S 67°19' W 45.96ft. marked C $\frac{1}{4}$ S6 BT

Nailed brass washer marked PLS 933 to BT blaze of trees.
Set steel post 4ft. South of corner. Used T-2 and steel tape, measuring a horizontal distance to the center of bearing trees.

REGISTERED
PROFESSIONAL
LAND SURVEYOR
David H Krumbein
OREGON
JULY 17, 1970
DAVID H. KRUMBEIN
933

T 7S R 33E
C $\frac{1}{4}$ —— S6
1978
PLS 933

Office of County Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 20 day of Sept 1978
Robert D. Bagett by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-71)0-57 (9/71)

☆ GPO 796-333

C-3

See Remon Dated Aug 1990