CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:
Center quarter corner, Sec. 6, T.7S., R.33E., W.M.
Corner not set in original survey of township.

Corner set in 1978 by PLS 933.
His record reads:
Set 2 1/2" x 30" iron pipe 26" in ground with brass cap marked as shown from which I scribed bearing trees A pine 11 in. diam. bears N 29°51' E 49.25 ft. marked C 1/4 S6 BT. A pine 12 in. diam. bears S 67°19'W 45.96 ft. marked C 1/4 S6 BT.
In 1991, PLS 1341, added a new bearing tree to this corner. His record reads:
A pine, 14" diam., bears S.31°55'W., 22.50', scribed C1/4 S6 BT.

Index: C-3

1	DIAGRAM	1
1	Brass Cap	1
1		1
1		1
1	T7S R33E	1
1	C1/4---S6	1
1	1978	1
1		1
1	PLS 933	1
1		1

Description of corner evidence found:
Found the corner monument as described from which:
A 12" dbh Ponderosa Pine bears N31 3/4°E, 49.2' with healed blaze.
A 14" dbh Ponderosa Pine bears S68°W, 46.0' with healed blaze.
A 14" dbh Ponderosa Pine bears S32 1/2°W, 22.5' with visible scribe.

Description of monument and accessories I established to perpetuate the original location of this corner:
Cleared brush and debris from corner and set new bearing tree as follows:
A 13" dbh Douglas Fir bears N53°W, 34.8' scribed C1/4 S6 BT.
The bearings are true based on the GPS bearings to the surveyed steel post which bears S88 1/2°E, 43.4'.
An aluminum washer stamped RLS 852 is nailed between the letters B and T. on the new tree. All the BT's have LSM and BT signs attached.
Painted 6" red bands around all the trees and painted the scribe blazes red.

This work was done May 25, 1994.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

David L. Haddock

OREGON
JULY 12, 1968
DAVID L. HADDOCK
852

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 26 day of July, 1994.

Robert D Bagott by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)