CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

The corner was originally established by Eugene McCornack under Contract No. 398 dated July 2, 1882.

The original notes state that at the corner:

A 4 in. square by 4 ft. marked post, set 24 in. in the ground for the corner, from which:

A 8 in. dia. Pine bears N35°E - 14 lks (9.2 ft.) marked: T7S R35½E S9 BT

A 8 in. dia. Pine bears S35°E - 31 lks (20.5 ft.) marked: T7S R35½E S16 BT

DIAGRAM



For history of 1974 BLM remonumentation, see attached sheet.

Description of corner evidence found:

A 3¼ in. brass cap on an iron pipe, protruding 10 in. out of the ground, set by BLM in 1974, marked as per diagram, from which:

A 5½ in. dia. Lodgepole Pine bears N36°E - 9.9 ft. with visible scribing.

A 9 in. dia. Lodgepole Pine bears S35°E - 20.5 ft. with visible scribing.

Description of monument and accessories I established to perpetuate the original location of this corner:

Attached 54-3 and 54-4 signs to bearing trees. Painted the face of the blaze and a 6 in. band around each bearing tree red.

Set a steel fence post, with 54-2 and 54-4 signs attached, South of the monument.

Used a steel tape and a magnetic staff compass, with 20° East declination. Measured to the center of the bearing trees.

This corner was maintained on September 15, 1983.

Witnessed by: Robert D. English
Aaron C. Hoeft

REGISTERED
PROFESSIONAL
LAND SURVEYOR

William R. Wells

OREGON
JULY 22, 1977
WILLIAM R. WELLS
1106

Office of County Surveyor *County of* Grant

State of Oregon, *I hereby certify that the within instrument was filed in this office for record on the* 15 *day of* Oct, *19* 83

Robert D. Enyart *by* .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆GPO—798-276

J-9