CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner not previously established.

DIAGRAM

T7S R35½E
SE-SW
1/64 S34
1983
PLS848

Description of corner evidence found:

N/A

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30"x2½" aluminum pipe with a 2½" aluminum cap stamped as shown in diagram.
Set 22" in the ground.
From which:
A Fir 10" dia. bears S86°W, 30.3 ft. scribed SE-SW 1/64 S34 BT.
A Lodge-pole Pine 7" dia. bears S60°E, 26.7 ft. scribed SE-SW 1/64 S34 BT.
Set steel post with warning signs North 5 ft. and East 8 ft.
Nailed brass washers stamped PLS848, bearing tree and warning signs to each tree.
Painted 6" red band around each tree.

Corner monumented 8-30-83
Witnessed by Dan Martin

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Douglas M. Ferguson

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Office of Summer County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 22 day of Nov, 19 83
Robert D. Bogert by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆GPO—798-276

Y½-14½