# CERTIFIED RECORD OF LAND CORNER MONUMENTATION

**History of original corner establishment:**

Corner not previously established.

**DIAGRAM**

T7S R35½E
C-S-S
1/64 S34
1983
PLS848

**Description of corner evidence found:**

N/A

**Description of monument and accessories I established to perpetuate the original location of this corner:**

Set a 30"x2½ aluminum pipe with a 2½" aluminum cap stamped as shown in diagram.
Set 22" in the ground.
From which:
A Fir 12" dia. bears N2°W, 15.6 ft. scribed C-S-S 1/64 S34 BT.
A " 13" " " S68°E, 30.5 ft. " " " " "
Set steel posts with warning and boundry signs South 4 ft. and West 4 ft.
Nailed brass washers stamped PLS848, bearing tree and warning signs to each tree.
Painted 6" red band around each tree.

Corner monumented 8-30-83

Witnessed by Dan Martin

REGISTERED PROFESSIONAL LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 22 day of Nov, 19 83
Robert D Baggett by .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆GPO—798-276

Y½-15