CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner not previously established.

DIAGRAM

T7S R35½E
C-S-S-S
1/256 S34
1983
PLS848

Description of corner evidence found:

N/A

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30"x2½" aluminum pipe with a 2½" aluminum cap stamped as shown in diagram.
Set 22" in ground.
From Which:
A Tamarack 20" dia., forked at breast height bears S10°E, 422 ft. scribed C-S-S-S ½56 S34 BT.
A " 12" " " N7°E, 40.4 ft. " " " " " "
Set steel posts with warning & boundry signs North and East 5 ft.
Nailed brass washers stamped PLS848, bearing tree and warning signs to each tree.
Painted 6" red band around each tree.

Corner monumented 8-31-83

Witnessed by Dan Martin

REGISTERED PROFESSIONAL LAND SURVEYOR
OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 22 day of Nov, 19 83
Sherrill D Baggett by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆ GPO—798-276

Y 3/4 - 15