


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

J-23

History of original corner establishment:

1884, Herman D. Gradon, under contract 499, established the corner. He set a post 3' long 3" square, 24" in the ground, from which:
5" Fir bears, N. 25° W., 32 lks.
4" Fir bears, S. 36° W., 18 lks.



Description of corner evidence found:

NONE

Description of monument and accessories I established to perpetuate the original location of this corner:

Finding no evidence of the corner I set at proportionate distance a 2 1/2" by 30" aluminum pipe, with a 3 1/4" aluminum cap, 28" in the ground, from which:
10" Western Larch bears, N. 47 1/4° E., 28.6 feet, marked "1/4 S12" "BT".
5" Lodgepole Pine bears, S. 17° E., 11.4 feet, marked "1/4 S13" "BT".
6" Lodgepole Pine bears, S. 29 3/4° W., 20.5 feet, marked "1/4 S13" "BT".
6" Western Larch bears, N. 22 3/4° W., 21.7 feet, marked "1/4 S12" "BT".

The BT's are double blazed and have a brass washer stamped "RLS 2308" nailed to the lower blaze by the "BT" scribing.

Magnetic Declination: 20° East

Work performed by: David A. Schlaich (RLS 2308)
Witnessed by: Troy Allen, Ira McCauley & Shane Sills

Date: September, 1993

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

David A Schlaich

OREGON
JULY 16, 1997
DAVID A. SCHLAICH
2308

Expires 12/31/94

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 2 day of Feb, 1994
Robert D. Boyert by _____
(COUNTY OFFICIAL) (DEPUTY)