


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

E-5

History of original corner establishment:

1884, Herman D. Gradon, under contract No. 499, established the corner. He set a wood post, 4' long by 4" square, 24" in the ground, from which:

- 9" Tamarack bears, N. 80° E., 31 lks.
- 12" Tamarack bears, S. 30° E., 15 lks.
- 8" Tamarack bears, S. 39° W., 29 lks.
- 11" Tamarack bears, N. 28° W., 19 lks.



Description of corner evidence found:

Found three of the BT's:

- 13" Western Larch snag bears, S. 30° E., 9.9 feet, chopped open to scribing.
- 7" windthrown Western Larch snag bears, S. 39° W., 19.1 feet, with scribing visible on partially healed blaze.
- 19" Western Larch bears, N. 20° W., 12.5 feet, with healed blaze.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the intersection of the record distances, I set a 2 1/2" by 30" aluminum pipe, with 3 1/4" aluminum cap, 24" in the ground.

Marked New BT's:

- 16" Western Larch bears, N. 77° E., 33.7 feet, marked "T8S R34E S5""BT".
- 8" Western Larch bears, S. 36° E., 15.1 feet, marked "T8S R34E S8""BT".
- 7" Western Larch bears, S. 46° W., 30.0 feet, marked "T8S R34E S7""BT".

New BT's are double blazed and have a brass washer stamped "RLS 2308" nailed to the lower blaze by the "BT" scribing.

Magnetic Declination: 20° East

Worked performed by: David A. Schlaich (RLS 2308)

Witnessed By: Shane Sills

Date: June, 1993

**REGISTERED  
PROFESSIONAL  
LAND SURVEYOR**

*David A. Schlaich*

OREGON  
 JULY 16, 1987  
**DAVID A. SCHLAICH**  
 2308

*Expires 12/31/94*

Office of Surveyor County of Grant  
 State of Oregon, I hereby certify that the within instrument was filed in this office  
 for record on the 2 day of Feb, 1994  
Robert D. Ragan by \_\_\_\_\_  
 (COUNTY OFFICIAL) (DEPUTY)