CERTIFIED RECORD OF LAND CORNER MONUMENTATION

E-05

History of original corner establishment:

1884, HERMAN D. GRADON, UNDER CONTRACT NO. 499, ESTABLISHED THE CORNER. HE SET A POST 4' LONG & 4" SQUARE, 24" IN THE GROUND, FROM WHICH:
9" TAMARACK, N. 80° E., 31 LINKS.
12" TAMARACK, S. 30° E., 15 LINKS.
8" TAMARACK, S. 39° W., 29 LINKS.
11" TAMARACK, N. 28° W., 19 LINKS.

1993, DAVID A. SCHLAICH, RLS 2308, FOUND THE SE, SW, & NW BT'S AND SET AT THE INTERSECTION OF THE RECORD DISTANCES A 2 1/2" BY 30" ALUMINUM PIPE, WITH 3 1/4" ALUMINUM CAP, 24" IN THE GROUND, FROM WHICH:
13 WESTERN LARCH, S. 30 E., 9.9 FEET, CHOPPED OPEN TO REVEAL SCRIBING.
7" WINDTHROWN WESTERN LARCH SNAG, S. 39° W., 19.1 FEET, WITH SCRIBING VISIBLE ON A PARTIALLY HEALED BLAZE.
19" WESTERN LARCH, N. 20° W., 12.5 FEET, WITH HEALED BLAZE.
MARKED NEW BT'S:
16" WESTERN LARCH, N. 77° E., 33.7 FEET.
8" WESTERN LARCH, S. 36° E., 15.1 FEET.
19" WESTERN LARCH, S. 46° W., 30.0 FEET.

DIAGRAM



Description of corner evidence found:

FOUND A 2 1/2" ALUMINUM PIPE, WITH 3 1/4" ALUMINUM CAP, PROJECTING 6" OUT OF THE GROUND, MARKED AS SHOWN (SEE DIAGRAM), FROM WHICH:

16" WESTERN LARCH, N. 77° E., 33.7 FEET, SCRIBING "T8S R34E S5""BT" VISIBLE ON DOUBLE BLAZE (1993 BT).
8" WESTERN LARCH, S. 36° E., 15.1 FEET, SCRIBING "T8S R34E S8""BT" VISIBLE ON DOUBLE BLAZE (1993 BT).
13" WESTERN LARCH SNAG, S. 30° E., 9.9 FEET, WITH HEALED BLAZE CHOPPED OPEN TO REVEAL SCRIBING (ORIGINAL BT).
7" WINDTHROWN WESTERN LARCH SNAG, S. 39° W., 19.1 FEET, WITH SCRIBING ON PARTIALLY HEALED BLAZE (ORIGINAL BT).
7" WESTERN LARCH, S. 46° W., 30.0 FEET, WITH SCRIBING "T8S R34E S7""BT" VISIBLE ON DOUBLE BLAZE (1993 BT).
19" WESTERN LARCH, N. 20° W., 12.5 FEET, WITH HEALED BLAZE (ORIGINAL BT).

THE 1993 BT'S HAVE A 3/4" BRASS WASHER STAMPED "RLS 2308" NAILED TO THE LOWER BLAZE BETWEEN THE "BT" SCRIBING.

Description of monument and accessories I established to perpetuate the original location of this corner:

NAD83(1991)
LATITUDE: 44°53'43.91321" NORTH
LONGITUDE: 118°39'24.01581" WEST

MAGNETIC DECLINATION: 20° EAST

WORKED PERFORMED BY: DAVID A. SCHLAICH
DATE: JULY, 1995

REGISTERED
PROFESSIONAL
LAND SURVEYOR

David A Schlaich

OREGON
JULY 16, 1987
DAVID A. SCHLAICH
2308

RENEWS 06/30/96

Office of Surveyor County of Grant

State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 6 day of Oct, 19 95

Robert D Bagott by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

See MAP of Survey 1383 E-05