


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

**History of original corner establishment:**

Original survey by Herman D. Gradon, Contract No. 499, 1884.  
Set a post 3 ft. long 3 ins. square 24 ins. in ground for  
1/4 Sec. Cor. from which:

A Pine 28" dia. bears N12°W 45 lks. dist. marked 1/4 S BT.

A Pine 36" dia. bears S27°E 45 lks. dist. marked 1/4 S BT.



**Description of corner evidence found:**

A Ponderosa Pine stump with bottom part of blaze and old axe marks. Stump is 34" dia. and blaze was made at about 26" dia., S21.

A Ponderosa Pine stump 44" dia. at record distance and bearing with no blaze. Low cut when logged. Location matches reasonably well with creek call (454 ft) 465 ft. to the west.

(Both stumps have resulted from logging operations.)

**Description of monument and accessories I established to perpetuate the original location of this corner:**

At record bearing and distance from two original BT stumps we set 2 1/2" x 30" galvanized iron pipe 24" in ground with mound of stone and dirt to top of pipe with 3" brass cap attached stamped:

From which:

The original BT's - A 44" Ponderosa Pine stump bears S27°E 29.7 ft.

A 34" Ponderosa Pine stump bears N12°W 29.7 ft.

New BT's - A Ponderosa Pine 28" dia. bears N65°E 57.4 ft. scribed 1/4 S21 BT.

A Ponderosa Pine 11" dia. bears S53°E 25.9 ft. scribed 1/4 S28 BT.

Attached brass washers stamped LS 1099 to foot blaze of new BT's.

Corner established and perpetuated in accordance with our contract No. 53-04R3-2-01275.

Magnetic compass (18° East declination)

Steel Tape

T8S R35E  
1 S21  
4 ———  
S28  
PLS 1099  
1982

October 5, 1982

Witnesses: Glen Wagoner  
Greg Orton  
Kevin Sandquist



Office of Surveyor County of Grant  
State of Oregon I hereby certify that the within instrument was filed in this office  
for record on the 2 day of Feb, 1983  
Robert W. Bapitt by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)