CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

None

DIAGRAM

T8S R35E
S-N-S 1/256

S28 | S27

PLS 1099
1983

Description of corner evidence found:

None

Found unrecorded pin
0.4 ft. North
0.5 ft. West

Description of monument and accessories I established to perpetuate the original location of this corner:

At proportionate distance determined by survey set a 2 1/2"x30" galv. iron pipe with brass cap 29" in ground marked:
From Which:
A Lodgepole Pine 6" dia. bears S 70°E 26.6 ft. marked SNS 1/256 S27 BT.
A Lodgepole Pine 8" dia. bears S 61°W 51.7 ft. marked SNS 1/256 S28 BT.

T8S R35E
S-N-S 1/256

S28 | S27

PLS 1099
1983

Attached brass washers stamped LS 1099 to BT blaze on both trees.

Corner perpatuated in accord. with Umatilla N.F.survey contract no. 53-04R3-2-01275.

20° East Declination Steel Tape Post East w/54-2 & 54-9 Post West w/54-2

Falls in clearcut 350'± South of Granite Creek.

September 1, 1983 Witnesses: A. Ray Crapo
Greg Orton
Kyle McKinney

Refer to Grant County Survey No. 828

REGISTERED
PROFESSIONAL
LAND SURVEYOR
Gary L. Langlitz
OREGON
JULY 22, 1977
GARY L. LANGLITZ
1099

Office of SURVEYOR County of GRANT
State of OREGON, I hereby certify that the within instrument was filed in this office for record on the 30 day of AUG, 1984
Robert D Smith by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆ GPO—798-276

T3/4-13