

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

T-18

History of original corner establishment:

None. Corner established by this survey.

DIAGRAM

T8S R35E
W 1/16
C-----C
S26
1996
PLS 1106

Description of corner evidence found:

None.

Description of monument and accessories | established to perpetuate the original location of this corner:

At position established by survey set a 2 1/2" diameter aluminum pipe 30" long with a 2 1/2" aluminum cap, projecting 4" out of a surrounding mound of stone (marked as shown in corner diagram).

Set a steel fence post alongside with signs 54-2 and 54-9 attached.

New Accessories:

A 6" diameter western larch bears S 35° W, 46.6 feet marked "CW1/16S26BT" on double blaze.

A 8" diameter lodgepole pine bears N 85 1/2° W, 59.9 feet marked "CW1/16S26BT" on double blaze.

Each new bearing tree has signs 54-3 and 54-9 attached below a 6" band of red paint. Each blaze painted red with a brass washer stamped "PLS 1106" attached.

Compass declination 18° East.

Witnessed by: William L. Hanley, PLS
Kelly Snively

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Will R. Wells

OREGON
JULY 22, 1977
WILLIAM R. WELLS
1106

Renews 6/30/98

Office of SURVEYOR County of GRANT
State of OREGON, I hereby certify that the within instrument was filed in this office
for record on the 8 day of DEC, 1996
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)