


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original GLO survey by Herman D. Gradon, Contract No. 499, dated March 11, 1884. Record states: Set a post 4 ins. sq. 4 ft. long 24 ins. in ground for cor. to secs. 26, 27, 34 & 35 marked T.8S.S.26 on N.E. R.35 E.S.35 on S.E. S.34 on S.W. & S.27 on N.W. faces, with 1 notch on S. & 2 notches on E. edges: from which A pine 12 ins. dia. brs. N.58°E. 270 lks. dist. marked T.8S.R.35E.S.26B.T. A pine 7 ins. dia. brs. S.62°E. 266 lks. dist. marked T.8S.R.35E.S.35B.T. A pine 6 ins. dia. brs. S.16°W. 149 lks. dist. marked T.8S.R.35E.S.34B.T. A pine 8 ins. dia. brs. N.52°W. 224 lks. dist. marked T.8S.R.35E.S.27B.T. Corner perpetuated by Gary L. Langlitz, PLS 1099, Grant Co. Survey No. 828, dated 1983. Record states: No evidence found. At corner position determined by survey we set a 2 1/2"x30" galvanized iron pipe 26" in the ground.



Description of corner evidence found:

Found a 2 1/2" brass cap on a 2 1/2"x30" galvanized iron pipe lying on the ground. Re-established corner position as described in "Description of monument and accessories I established to perpetuate the original location of this corner:" From re-established corner position: A 10" dia. lodgepole pine, bears S78 1/2°E, 75.3' with scribing visible on a double blaze. (1983 BT) A 7" dia. dead and standing lodgepole pine bears N50°E, 73.9' with scribing visible on partly healed double blaze. (1983 BT) An 18" dia. lodgepole pine bears N83°W, 41.5' with scribing visible on partly healed double blaze. (1983 BT)

Description of monument and accessories I established to perpetuate the original location of this corner:

At position determined by using Langlitz record distances from the West 1/4 corner of Section 26 and the South 1/4 corner of Section 26 (2626.02 feet and 2627.73 feet respectively), I reset Langlitz monument, projecting 4 inches from a surrounding mound of stone. Set steel fencepost alongside with signs 54-2 and 54-9 attached.

New Accessories:

A 10" dia. lodgepole pine bears N 35° E, 57.25 feet marked "T8SR35ES26BT" on a double blaze. A 5/8" iron rod with a yellow plastic cap marked "OR PLS 1106, WA PLS 17372" bears S 55° W, 26.3 feet, steel fence post alongside with signs 54-3 and 54-9 attached. A 12" dia. lodgepole pine bears N 70° W, 34.2 feet marked "T8SR35ES27BT" on a double blaze.


Bearing trees have signs 54-3 and 54-9 attached below a 6" band of red paint. Blazes painted red with brass washer stamped "PLS 1106" attached to new bearing trees.

Compass declination 18° East.

Witnessed by: Kelly Snively



Will R. Wells



Office of Surveyor Grant County of Grant Renewal 6/30/98
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 18 day of Dec, 1996
Robert D. Boyett by (COUNTY OFFICIAL) (DEPUTY)