

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


History of original corner establishment:

The original survey in 1884 done by Herman D. Gradon under GLO Contract No. 499 set:

Post 3 ft. long 3 ins. sq. 24 ins. in ground for 1/4 sec. cor marked 1/4 S on N. face, from which:

A Pine 30 ins. dia. bears N65°E 49 lks. dist. marked 1/4 S BT.

A Pine 40 ins. dia. bears S38°W 30 lks. dist. marked 1/4 S BT.



Description of corner evidence found:

A 24" Ponderosa Pine stump. No visible scribing for S26 BT.


A 32" Pond. Pine snag with visible scribing 1/4 S BT for S35 BT. No evidence could be found of original corner post.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set: At position established from original bearings and distance of original BT's set a 2½"x30" galvanized pipe with brass cap stamped:

Pipe was set 22" in ground with mound of stone and dirt to cap. from which:

The original BT's, a 32" Ponderosa Pine snag bears S38°W 19.8 ft. A 24" Pond. Pine stump bears N65°E 32.3 ft.



New BT's

A Pond. Pine 10" dia. bears N82° W 54.3 ft., scribed 1/4 S26 BT.

A Pond. Pine 9" dia. bears S43½°W 35.6 ft., scribed "1/4 S35 BT".

Attached brass washers stamped LS 1099 to foot blaze of new BT's. Corner position monumented and perpetuated in accordance with Forest Service Contract No. 53-04R3-2-1275.

September 7, 1982

Clear, Warm

Steel Tape, Staff Compass
18°E Declination

Witnesses: G. Wagoner
G. Orton
G. Langlitz



Office of Surveyor County of Grant
 State of Oregon, I hereby certify that the within instrument was filed in this office
 for record on the 7 day of Feb, 1982
Robert D. Bartz by _____
 (COUNTY OFFICIAL) (DEPUTY)