


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established by Herman D. Gardon, GLO Contract No. 499, dated March 11, 1884. Record states: Set post 3 ft. long 3 ins. sq. 24 ins. in ground for 1/4 sec. cor. marked 1/4 S. on N. face, from which A pine 30 ins. dia. brs. N. 65° E. 49 lks. dist. marked 1/4 S.B.T. A pine 40 ins. dia. brs. S. 38° W 30 lks. dist. marked 1/4 S.B.T.



Corner maintained by Gary L Langlitz, PLS 1099, Grant County Survey No. 828, dated 1983. Record States: Evidence Found: A 24" Ponderosa Pine stump. No visible scribing for S26 BT. A 32" Pond. Pine snag with visible scribing 1/4 S BT for S35 BT. No evidence could be found of original corner post. Set: At position established from original bearings and distance of original BT's set a 2 1/2"x30" galvanized pipe with brass cap stamped: (as Description of corner evidence found).

Description of corner evidence found: A 2 1/2" brass cap on a 2 1/2" galvanized iron pipe in a surrounding mound of stone, steel fence post alongside with signs 54-2 and 54-9 attached. Original bearing trees: A 24" diameter sawed stump bears S 65° E, 32.3 feet with signs 54-3 and 54-4 attached. A 36" windblow snag bears S 38° W, 19.8 feet with open blaze and signs 54-3 and 54-4 attached. 1982 bearing trees: A 12" diameter ponderosa pine bears S 43 1/2° W, 35.6 feet with partially healed blaze and visible scribes. A 14" diameter ponderosa pine bears N 82° W, 54.3 feet with visible scribe marks on partially healed blaze, signs 54-3 and 54-4 attached.

Description of monument and accessories established to perpetuate the original location of this corner:

Maintenance to monument: Added more stones to mound. Attached sign 54-9 and repainted all found bearing trees. New bearing trees: A 9" diameter ponderosa pine bears N 31° E, 30.4 feet marked "1/4S26BT" on double blaze. An 8" diameter ponderosa pine bears S 66° E, 35.5 feet marked "1/4S35BT" on double blaze. Each bearing tree has signs 54-3 and 54-9 attached below a 6" band painted red. Blazes are painted red with a brass washer stamped "PLS 1106" attached to new bearing trees.

Compass declination 18° East.

Witnessed by: William L. Hanley, PLS Kelly Snively

REGISTERED PROFESSIONAL LAND SURVEYOR

William R. Wells

OREGON JULY 22, 1976 WILLIAM R. WELLS 1106

Renews 6-30-96

Office of Surveyor County of Grant State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 18 day of Dec, 1976 Robert D. ... by ... (COUNTY OFFICIAL) (DEPUTY)