Z-21

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

DIAGRAM

T8S R35E

S35 | S36

S2
T9S

Original survey by Herman D. Graydon in 1884 under G.L.O. contract No. 499 states:

Set a Basalt Stone 16x10x8 ins., 10 ins. in ground for Cor. to Sections 35 & 36 marked T8S, S36 on NE & R35E S35 on NW faces with 1 notch on the E and 5 notches on the W edges

From Which:

A Pine 10 ins. diam. bears N 81°W, 168 lks. dist. marked T8S R35E S35 BT.

No tree within limits N of Line in S36 hence set a raised mound of stone alongside.

Description of corner evidence found:

Found a 2" iron pipe, with brass cap, properly marked as established by William Hanley, L.S. 1639 (see Grant Co. Survey 575).

From Which the original N.W. bearing tree, now a decayed pine stump with scribing "BT" visible is located at record bearing and distance.

And BT's marked by Hanley:

A Pine, 8" dia. bears N2°E 106.0 ft., alive and in good condition.

A Pine, 8" dia. bears N15°W 95.5 ft., alive and in good condition.

Description of monument and accessories I established to perpetuate the original location of this corner:

New BT:

A 12" dia. L.P. Pine bears S50°E, 195.0 ft. scribed T9S R35E S2 BT. Attached brass washer stamped LS 1099 to BT blaze. (This BT is being established to aid in the perpetuation of this corner location.)

Compass 20°E Declination, Steel Tape

Sept. 15, 1982 Witnesses: Glen Wagoner
Greg Orton
Rod Scott

See survey filed separately

Refer to Grant County Survey No. 828

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 22, 1977
GARY L. LANGLITZ
1099

Office of SURVEYOR County of GRANT

State of OREGON, I hereby certify that the within instrument was filed in this office for record on the 30 day of AUG, 19 84

Robert D Bagett by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71) SEE REMON FILED 7/13/79

☆GPO—798-276

Z-21