

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established and monumented by Otis O. Gould, Surveyor, during a subdivision survey Group No. 179 dated July, 1937.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor., with brass cap marked (as shown in the diagram).

A pine 12 ins. diam. brs. N74°E, (48.8')74 lks. dist., marked 1/4 S20 BT
A pine 16 ins. diam. brs. N40°W, (35.0')53 lks. dist., marked 1/4 S19 BT

DIAGRAM

T8S R36E

1/4
S19 | S20

1937
GLO

Description of corner evidence found:

3/4" pipe with a 2 1/2" brass cap standing 8" out of the ground.
12" Lodgepole pine (Dead & Down)(Scribing Visible)(1937 BT) bears N73° 15'E, 49.0 feet,
19" Lodgepole pine (Good Condition)(Scribing Visible)(1937 BT) bears N39° 15'W, 35.1 feet.

Description of monument and accessories established to perpetuate the original location of this corner:

Maintained the monument by making sure it was firmly set in the ground. No mound because no available rock, from which a new BT is:

10" Lodgepole pine bears 59°E, 25.6 feet scribed 1/4 S20 BT

Attached BT and Attention signs to and painted a red band around each BT. Bearings were taken with a staff compass, using a declination of 18° 30'E, to the scribed blazes which were painted red. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground. Set a steel fence post 5 feet N of the corner with an Attention sign attached.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on August 7, 1985, I maintained the corner as herein described.

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 16 DAY OF OCT, 1985

Robert O. Smith Co. Sur.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Leland Lee Myers

OREGON
JULY 9, 1965
LELAND LEE MYERS
699