


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Z-9

History of original corner establishment:

This corner was originally established by Otis Gould, U.S. Cadastral Surveyor, under special instructions dated Nov. 27, 1935, during his surveys in July through October, 1937. The original notes state that at the corner a marked brass cap on a 2" diameter by 3' long iron post was set 12" in the ground to bedrock and surrounded with a mound of stone to the top from which:



A 20" pine bears N58°E-35 lks, marked T8S R36E S33 BT.
A 8" pine bears N51°W-26 lks, marked T8S R36E S32 BT.

Description of corner evidence found:

A 2½" brass cap on a 2" iron pipe protruding 20" from a stone mound from which:

A 22" white fir stump bears N61°E-23.1' with scribing visible on an open blaze.
A 13" white fir bears N55°W-16.0' with healed blaze.

Note: The original notes call the bearing trees pine.

Description of monument and accessories established to perpetuate the original location of this corner:


Built a mound of stone around the monument. From the monument:

A 11" white fir bears N25½°E-17.6' scribed T8S R36E S33 BT.

New bearing tree has a brass washer stamped PLS 1106 nailed to the face of blaze. Attached sign 54-3 and 54-9 and painted face of blaze and a 6" red band around each bearing tree. Set steel fence post East of corner and attached sign 54-9.

Used steel tape and staff compass with 20°E declination, measured to the center of the bearing trees.

The cap is a standard GLO brass cap marked:



This corner was maintained on September 19, 1985.

Witness: Bob English.

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

William R. Wells

**OREGON
JULY 22, 1977
WILLIAM R. WELLS
1106**

Office of...County Surveyor..... County of...Grant
Oregon
State of....., I hereby certify that the within instrument was filed in this office
for record on the...11... day of...Feb... 19...86
Robert V. Baggett by
(COUNTY OFFICIAL) (DEPUTY)