CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:
Original corner established by: Arron York, Deputy Surveyor, under Contract No. 309, dated November 18, 1878.

Surveyor General Record States: Set stone 16x12x8 inches, for 1/4 section corner, raised stone mound at corner.

CORNERSTONE SURVEYING INC
T7S R27E
S36
1/4
S1
T8S
2014

Description of corner evidence found:
Found stone 18x11x7 inches in a 4 ft. ring of stones, no chisel marks were visible. An ease-west fence is 4 feet north of the corner position.

RECEIVED AND FILED
GRANT COUNTY SURVEYOR
OCT 2 7 2014
BY:

REGISTERED
PROFESSIONAL
LAND SURVEYOR
OREGON
SEPT 19, 1995
JACK L. WATSON
2734
Renewal Date 6/30/2016

Description of monument and accessories set at corner location:
I accept the found stone for the corner position. I set a 2 1/2"x30" aluminum pipe with attached 3 1/4" aluminum cap, 12 inches in the ground, surrounded by a mound of stone to support the monument. Placed original marked stone north alongside pipe. The cap is stamped as shown in the diagram.

From which:
A 5/8"x30" iron pin bears N68°E, 6.35 feet, with attached red plastic cap marked CORNERSTONE SURVEYING INC.
A 5/8"x30" iron pin bears S44°E, 15.00 feet, with attached red plastic cap marked CORNERSTONE SURVEYING INC.
A 5/8"x30" iron pin bears S45°W, 22.47 feet, with attached red plastic cap marked CORNERSTONE SURVEYING INC.
A 5/8"x30" iron pin bears N43°W, 8.96 feet, with attached red plastic cap marked CORNERSTONE SURVEYING INC.

I used a steel tape and magnetic compass, with 14° E. declination.

Date: October 16, 2014.

Office of ..... County of .....
State of ....., I hereby certify that the within instrument was filed in this office for record on the ..... day of ....., 2014.
..... by .....
(COUNTY OFFICIAL) (DEPUTY)