CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:
Original corner established by: Aaron York, Deputy Surveyor,
under Contract No. 309, dated November 18, 1878.
Surveyor General Record States: Set stone 24x15x8 ins. for
¼ section corner raised mound of stone at corner.

T8S R27E
1/4

S15 | S14

LS2632
2013

Description of corner evidence found:
Found stone 24x14x8 inches set upright in a mound of stone
with a 3 ft base, 1 ft high, marked 1/4 on the east face. A fence
corner running south and west is 5 ft. south of the corner position.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 20, 1993
CARL J. STOUT
#2632

RENEWAL 6/14

Description of monument and accessories set at corner location:
I accept the marked corner stone position for this corner. I set a 2½"x30" aluminum pipe with attached 3½" aluminum cap, 10 inches in the ground, surrounded by a mound of stone with 3 ft. base to top of cap. Placed original marked stone north and alongside the pipe. The cap is stamped as shown in the diagram.

From which:
A 6" Juniper bears N85°E, 50.6 ft., marked XBT.
A 22" Juniper bears S55°E, 91.3 ft., marked 1/4S14BT.
A 12" Juniper bears S16°W, 77.5 ft., marked 1/4S15BT.
A 4" Juniper bears N78°W, 28.8 ft., marked XBT.

I used a steel tape measuring to a 50d nail driven in the side center at the root crown of the BT's and magnetic compass, with 14° E. declination.
Witness: Jack Watson, PLS
Date: April 4, 2013

Office of ....SURVEYOR.... County of ....GRANT....
State of ....OR...., I hereby certify that the within instrument was filed in this office
for record on the ..24.. day of ....APRIL...., 2013.
..... by .....
(COUNTY OFFICIAL) (DEPUTY)

L-17