# CERTIFIED RECORD OF LAND CORNER MONUMENTATION

**History of original corner establishment:**

***DIAGRAM***

T8S R27E
C 1/4 S21

**Description of corner evidence found:**

**Description of monument and accessories I established to perpetuate the original location of this corner:**

T8S R27E
C 1/4
S21
1992
LS 896

Set 2½"x30" alum. pipe with a 2½" alum. cap 22" in ground.
No stone available. Stamped:

Marked:

8" Pine--N23½W 24.5' Scribed C 1/4 S21 BT.
11" Pine--S6¼E 21.8' Scribed C 1/4 S21 BT.
8" Pine--S53E 36.4' Scribed C 1/4 S21 BT.
6" Pine--N15E 30.0' Scribed C 1/4 S21 BT.
Nailed 54-9 and 54-3 signs to BT's, painted bands and blazes red and nailed a 1" brass disk stamped PLS 896 flush between the B and the T.
Set guard post South with 54-9 sign.
Dec. 20.

REGISTERED PROFESSIONAL LAND SURVEYOR
OREGON
JULY 11, 1989
LARRY D. BISHOP
896

*Office of* Grant *County of* Oregon
*State of* Oregon, *I hereby certify that the within instrument was filed in this office for record on the* 20 *day of* Jan, *19* 93
Robert D. Bagott *by* .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

1248
GPO—798-276

P-11