CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This corner was originally established by Deputy Aaron F. York in 1878 under contract #309. Set stone 16"x16"x6". Raised stone mound at corner.

DIAGRAM

T8S R27E

S21	S22
S28	S27

Description of corner evidence found:

Fractured stone 16"x15"x6" (record above) sitting upright and supported on lower side by a small mound of stone at record distance East of Cupper Creek-find no identifiable grooves or notches. Stone is very near record bearing and distance East of 1/4 S21/S28.

Description of monument and accessories I established to perpetuate the original location of this corner:

Replaced stone with a 2½"x30" alum. pipe with a 2½" alum. cap 4" in ground in a mound of earth and stone 5' base to top. Stamped:
Buried original stone East and adjacent to monument.

T8S R27E
S21 | S22
S28 | S27
1992
LS 896

Marked:

12" Juniper--N44¼W 89.0' Scribed T8S R27E S21 BT.
20" Pine--S15¼W 10.2' Scribed T8S R27E S28 BT.
Chiseled BXO on East face 2'x2'x1' high exposed outcrop--N45E 12.0' to X.
Chiseled BXO on top 2'x1½'x1½' high exposed outcrop--S61½E 50.0' to X.
Nailed 54-9 and 54-3 signs to BT's, painted bands and blazes and chiseled areas red and nailed a 1" brass disk stamped PLS 896 flush between the B and the T.
Set guard post NE with 54-9 sign.
Dec. 20.

REGISTERED PROFESSIONAL LAND SURVEYOR
Larry D. Bishop
OREGON
LARRY D. BISHOP
896

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 20 day of Jan, 19 93
Robert D Bazett by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

GPO—798-276

1248

R-13