# CERTIFIED RECORD OF LAND CORNER MONUMENTATION

X-5

**History of original corner establishment:**

This corner was originally established by Deputy Aaron F. York in 1878 under contract #309.

Set stone 14"x12"x8" and raised a stone mound at corner.

**DIAGRAM**

T8S R27E

1/4 31 | 32

**Description of corner evidence found:**

Stone 13"x12"x7" (record above) marked 1/4 in a mound of stone.

**Description of monument and accessories I established to perpetuate the original location of this corner:**

T8S R27E
1/4
S31 | S32
1993
LS 896

Set 2½"x30" alum. pipe with a 2½" alum. cap 22" in ground in a mound of stone and earth 3' base to top. Stamped:

Marked:

8" Juniper S83¼W--35.7' Scribed 1/4 S31 BT.
20" Juniper S37¼E--55.6' Scribed XBT.
20" Juniper S74E--46.1' Scribed 1/4 S32 BT.
12" Juniper N13½E--57.8' Scribed 1/4 S32 BT.
Nailed 54-3 and 54-9 signs to BT's, painted bands and blazes red and nailed a 1" brass disk stamped PLS 896 flush between the B and the T.
Set guard posts North and South with 54-2 and 54-9 signs.
Buried original stone SE of monument.
Dec. 20.

REGISTERED PROFESSIONAL LAND SURVEYOR

Larry D. Bishop

OREGON
JULY 11, 1980
LARRY D. BISHOP
896

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 12 day of Nov, 19 93
Robert D. Bagett by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

GPO—798-276

See M051292

X-5