CERTIFIED RECORD OF LAND CORNER MONUMENTATION

J-03

History of original corner establishment:

1884, HERMAN D. GRADON, UNDER CONTRACT NO. 499, ESTABLISHED THE CORNER. HE SET A POST 3' LONG & 3" SQUARE, 24" IN THE GROUND, FROM WHICH:
7" PINE, N. 21° E., 12 LINKS.
7" PINE, S. 35° E., 12 LINKS.

DIAGRAM



Description of corner evidence found:

NONE:

Description of monument and accessories I established to perpetuate the original location of this corner:

FINDING NO EVIDENCE OF THE ORIGINAL CORNER I SET BY SINGLE PROPORTION A 2 1/2" BY 30" ALUMINUM PIPE, WITH A 3 1/4" ALUMINUM CAP, 15" IN THE GROUND SURROUNDED BY A STONE MOUND 2' DIAMETER BY 16" HIGH, MARKED AS SHOWN (SEE DIAGRAM),
FROM WHICH:

20" ENGLEMANN SPRUCE, N. 1 3/4° E., 40.3 FEET, SCRIBED "1/4 S7""BT".
7" WHITE FIR, S. 61 3/4° E., 12.7 FEET, SCRIBED "1/4 S18""BT".
17" ENGLEMANN SPRUCE, S. 19 1/4° W., 42.4 FEET, SCRIBED "1/4 S18""BT".
15" WESTERN LARCH, N. 19 1/2° W., 41.6 FEET, SCRIBED "1/4 S7""BT".

THE BT'S ARE DOUBLE BLAZED AND HAVE A 3/4" BRASS WASHER STAMPED "RLS 2308" NAILED TO THE LOWER BLAZE BETWEEN THE "BT" SCRIBING.

NAD83(1991)
LATITUDE: 44°52'51.70230" NORTH
LONGITUDE: 118°40'01.39770" WEST

MAGNETIC DECLINATION: 20° EAST

WORKED PERFORMED BY: DAVID A. SCHLAICH
WITNESSED BY: RACHELLEL (SHELLY) FLETCHER
DATE: AUGUST 31, 1995

REGISTERED
PROFESSIONAL
LAND SURVEYOR

David A Schlaich

OREGON
JULY 16, 1987
DAVID A. SCHLAICH
2308

RENEWS 06/30/96

Office of Surveyor *County of* Grant

State of Oregon, *I hereby certify that the within instrument was filed in this office for record on the* 6 *day of* Oct, *19* 95

Robert D. Bagott *by*
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

See Map of Survey 1383

J-03