# CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner not previously established

NOTE

This monument marks the Wilderness Boundary within the National Forest Lands, only.

**DIAGRAM**

T8S R34E 3032




Description of corner evidence found:

Corner not previously established

Description of monument and accessories I established to perpetuate the original location of this corner:

sect. 28, I set a 2½" x 30" aluminum pipe with aluminum cap marked as shown, 26 inches in the ground, from which; At a point on the 6640 foot contour line, in the NE 1/4 of

Bearing Trees;
A 7" Spruce, bears N 5 E, 9.03 feet marked WB 3032 BT
A 12" White Fir, bears S 60 E, 9.97 feet marked WB 3032 BT.

Painted a 6 inch red band around all BTs and attached BT tags.

Set a steel fencepost approximately 5 feet West with signs attached.

I hereby certify that the above corner point was established as hereon described on August 2, 1990.

Witness: Jeff Petersen
Jim Bennett
Larry Pitcher

USDA FOREST SERVICE
WILDERNESS BOUNDARY

NO 3032

EL 6640
OPLS 644 1990

UNLAWFUL TO DISTURB

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 10, 1964
DUANE I. GRIFFITH
644

I used a steel tape and magnetic compass in the establishment of new accessories. I used 19° magnetic declination. The distances are to a 50d spike driven in the right side of the root crown. I attached a brass washer marked OPLS 644 to the BT blaze.

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 27 day of Sept, 19 90
Count R. Bagon by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)



WB