

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established by Rufus S. Moore, US Deputy Surveyor, during the original survey Contract No. 382 dated March, 1881.

DIAGRAM

T9S R31E

1/4

S16 | S15

1989
PLS 699

Set a basalt stone 18x12x6 for 1/4 sec. cor. from which a

- Pine 36 ins. diam., bears S10°E, (17.82') 27 lks. dist.
- Pine 30 ins. diam., bears S37°W, (50.16') 76 lks. dist.

Description of corner evidence found:

Found a couple of stones of near record size on a steep hillside that has had logging activity on it. Any rock not firmly set in the ground would be down the hill from its true position.

- Badly deteriorating stump Ponderosa pine (24" high)(Blaze in Rotted Remains)(1881 BT) bears at record.
- 28" Ponderosa pine (Poor Condition)(Blaze Opened by Others)(1881 BT) bears S37°30'W, 49.0 feet.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 2 1/2" aluminum cap, marked as shown in the diagram, 24" in the ground, at the point determined by the bearing trees. Built a mound of rock to be 36" in diameter by 6" high around the monument, from which new BTs are:

- 16" Ponderosa pine bears N58°E, 38.7 feet scribed 1/4 S15 BT
- 8" Ponderosa pine bears N72°W, 15.4 feet scribed 1/4 S16 BT
- A Blue DEEP buried 6" in the ground bears S58°W, 2.0' with a brass washer inside stamped PLS 699
- A Pink DEEP buried 8" in the ground bears S72°E, 2.0' with a brass washer inside stamped PLS 699

Attached BT and Attention signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being the bearing between corners G-13 and N-13 as shown on Grant County Map of Survey No. 634, to stamped brass washers nailed in the scribed red-painted blazes. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set steel fence posts 5 feet N and 5 feet S of the corner on the National Forest boundary lines. Attached Forest Boundary signs to each post and an Attention sign to the N post.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on November 12, 1989, I monumented the corner as herein described.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 9, 1965
LELAND LEE MYERS
699

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR
THIS 26 DAY OF July, 1990

Robert D. Baggett
Grant County Surveyor